

CUMMINS DIESEL GENERATOR SET

MC550

550 kVA

INDUSTRIAL GENERATOR

Reliable diesel generating set configured for prime, standby and project-specific industrial power applications.



STANDBY POWER

550 kVA

PRIME POWER

500.0 kVA

ENGINE MODEL

KTA19-G3A

FREQUENCY

50 Hz

GENERATOR OUTPUT

Standby Power	550 kVA
Prime Power	500.0 kVA
Standby Output	440.0 kW
Prime Output	400.0 kW
Frequency	50 Hz
Voltage	400 V
Phases	3
Power Factor	0.8

ENGINE

Engine Brand	Cummins
Engine Model	KTA19-G3A
Cylinders	6 Inline
Displacement	19.0 L
Air Intake	Turbocharged & Intercooled
Speed	1500 rpm
Governor System	Electronic
Cooling System	Water Cooling

TECHNICAL SPECIFICATIONS

Published product data for the selected generator model. Final component selection is confirmed with the commercial offer.

ALTERNATOR & CONTROL

Alternator	MKT / Stamford / Leroy Somer
Controller	Deep Sea Controller
Voltage Regulation	±1%
Insulation Class	H
Protection Standard	IP23
Generator Type	Silent / Open

FUEL SYSTEM

Fuel Type	Euro Diesel
100% Load	107.0 L/h
75% Load	82.3 L/h
50% Load	56.4 L/h
Canopy Fuel Tank	1100 L
Open Fuel Tank	1100 L

DIMENSIONS & WEIGHT

Canopy Dimensions	4600 x 1600 x 2700 mm
Canopy Weight	5085 kg
Open Dimensions	3900 x 1600 x 2950 mm
Open Weight	4410 kg

AVAILABLE PROJECT OPTIONS

- 50 Hz and 60 Hz configurations
- Silent canopy or open-frame execution
- Deep Sea, ComAp or SmartGen control solutions
- ATS, synchronization and remote monitoring systems
- Custom voltage, fuel tank and enclosure requirements